



(19)

(11) Publication number: **2000100450 A**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **10266206**(51) Intl. Cl.: **H01M 6/42 H01M 2/14**(22) Application date: **21.09.98**

(30) Priority:

(43) Date of application  
publication: **07.04.00**(84) Designated contracting  
states:(71) Applicant: **MATSUSHITA ELECTRIC IND CO  
LTD**(72) Inventor: **ISHIDA TSUTOMU**

(74) Representative:

**(54) LAYERED DRY  
BATTERY**

(57) Abstract:

**PROBLEM TO BE SOLVED:** To provide a layered dry battery excellent in shelf life and leakage resistance by forming a wax layer around a cell stack stacked with multiple unit cells, and enveloping the outside with a heat shrinkable resin tube to improve the sealing of the cell stack.

**SOLUTION:** Multiple unit cells 5 are stacked, a carbon-tin plate coupled positive electrode current collector 6 is installed on the uppermost unit cell 5 to form a stack, a wax layer 7 is formed around the stack, and the outside is enveloped with a heat shrinkable resin tube 8 to form a layered dry battery. An elastic seal member 9 is inserted at least into the gap between the upper opening section of the heat shrinkable resin tube 8 and snap terminals 10 combined with a positive and a negative electrode terminals.

COPYRIGHT: (C)2000,JPO

BEST AVAILABLE COPY

